

Industrial USB 2.0 Hub, 7-Port

www.vpi.us/usb-hubs/usb2-hub-industrial-1501

- Connect up to seven USB 2.0 self-powered and/or bus-powered USB peripheral devices (security cameras, printers, scanners, touch screen monitors, game controllers, flash drives, keyboards, mice, etc.).
- Ideal for industrial applications in harsh environments at high temperatures up to 158°F (70°C).
- Compliant with USB 2.0 high-speed specifications.
 - Backwards compatible with USB 1.1/1.0
 - Supports high-speed (480 Mbps), full-speed (12 Mbps), or low-speed (1.5 Mbps) USB devices.
- Each port supports full 500mA current.
- Supports Plug-n-Play specification.
- Hot-swappable.
- Cascade hubs to connect up to 127 devices.
- No drivers required.
- Integrated mounting brackets for easy surface/wall mounting.
- High quality, rugged steel construction with durable powder coat finish.



USB2-HUB-IND-7

The Industrial USB 2.0 7-Port Hub connects up to seven USB 2.0 high-speed peripheral devices to a PC or MAC computer in a harsh environment.

Specifications

Connectors

- Seven female USB Type A connectors.
 - Supports high-speed (480 Mbps), full-speed (12 Mbps), or low-speed (1.5 Mbps) USB devices.
- One female USB Type B connector.
 - Supports USB-enabled computers (PC and MAC).

Power

- Input: 100 to 240 VAC at 50 or 60Hz via AC adapter (included).
- Output: 5VDC, 8A
- Each port supports full 500mA current.
 - Overcurrent protection for each downstream port.

Environmental

- Operating temperature: 32°F to 158°F (0°C to 70°C).
- Storage temperature: -22°F to 185°F (-30°C to 85°C).
- Operating/storage relative humidity: 10 to 90% non-condensing RH.

Dimensions

- WxDxH (in): 6.50x2.09 x0.88 (165x53x22 mm).

MTBF

- 354,359 hours

Regulatory Approvals

- CE, FCC, RoHS
- TAA compliant

Package Includes

- 7-Port USB 2.0 Hub
- Power adapter
- 1 ft (305 mm) USB 2.0 male Type A to male Type B male cable.