



NOTE:

1. CABLE: {(28AWG X 3COAX, EACH COAX SPIRAL SHIELDED, 75Ω□, COLOR CODE: RED, GREEN, BLUE) + (24AWG X 2PAIRS + 24AWG X 4C)}, OVERALL: AL-FOIL AND BRAID(85%MIN) SHIELDED WITH A DRAIN WIRE, UL2919, BLACK (BK) PVC JACKET.
2. CONNECTOR: P1 & P2: HIGH DENSITY D-SUB 15PIN MALE: THE 9TH UNLOADED, SOLDER TYPE, GOLD FLASH CONTACTS, BLACK PBT INSULATION.
3. BLACK METAL SCREW. (MATERIAL: STEEL)
4. THUMB SCREW TO BE MOLDED BLACK (BK) ABS.
5. SHIELDING: COPPER-FOIL TAPE COVER PREMOLD AND 360 SOLDER TO CONNECTOR SHELL AND CABLE BRAID.
6. ALL HOOD MOLDED BLACK (BK) PVC.
7. TESTING: 100% ELECTRICAL TRST: 1M OHM/MAX INSULATION RESISTANCE. 3 OHM/MIN CONTACTOR AT DC 300V
8. PACKING: EACH CABLE IN A PRINTED POLY-BAG. LABEL (WHITE BACKGROUND WITH BLACK LETTERS) TO BE STAMPED ON THE PRINTED *TNT* POLY-BAG

PIN OUT

