

PIN ASSIGNMENT:

HDMI AM	HDMI AF
3	3 TMDS data2-
1	1 TMDS data2+
2	2 TMDS data2 Shield
6	6 TMDS data1-
4	4 TMDS data1+
5	5 TMDS data1 Shield
9	9 TMDS data0-
7	7 TMDS data0+
8	8 TMDS data0 Shield
12	12 TMDS Clock-
10	10 TMDS Clock+
11	11 TMDS Clock Shield
17	17 DDC/CEC Ground
13	13 CEC
15	15 SCL
16	16 SDA
14	14 Reserved
18	18 +5V Power
19	19 Hot Plug Detect
SHELL	SHELL

ORDERING INFORMATION:

19 01158 - * * *
 [1] [2] [3] [4] [5]

[1] SERIES NUMBER:
 19:Adapter Series

[2] SEQUENCE NO.:

01158(EX. 01001-01999):HDMI (A)MALE TO
 (A)FEMALE ADAPTER(270 DEGREE)

[3] OUTER MOLDING COLOR CODES:
 3:Black

[4] Plating of contact&shell:

1:Contact plated gold 15u";Shell plated G/F
 2:Contact plated gold 30u";Shell plated G/F

[5] SUFFIX NO.:

A:WITHOUT HDMI LOGO

RoHS Compliant

ELECTRICAL CHARACTER:

- 1)100% OPEN&SHORT TESTING
- 2)WITHSTANDING VOLTAGE:DC 300V 0.01Sec
- 3)INSULATION RESISTANCE:10M Ohm(Min)
- 4)CONDUCTIVE RESISTANCE:2 Ohm(Max)

VPI VIDEO
 PRODUCTS
 INCORPORATED

1275 Danner Drive Aurora, Ohio 44202
 Tel: 1-800-626-7801 Fax: 330-562-1999
 www.vpi.us sales@vpi.us