



ELECTRICAL CHARACTER:

- 1) 100% OPEN&SHORT TESTING
- 2) WITHSTANDING VOLTAGE:DC 300V 0.01Sec
- 3) INSULATION RESISTANCE:10M Ohm(Min)
- 4) CONDUCTIVE RESISTANCE:2 Ohm(Max)

PIN ASSIGNMENT:

HDMI 19M(A)	HDMI 19F(B)
3	3 TMDS data2-
1	1 TMDS data2+
2	2 TMDS data2 Shield
6	6 TMDS data1-
4	4 TMDS data1+
5	5 TMDS data1 Shield
9	9 TMDS data0-
7	7 TMDS data0+
8	8 TMDS data0 Shield
12	12 TMDS Clock-
10	10 TMDS Clock+
11	11 TMDS Clock Shield
17	17 DDC/CEC Ground
13	13 CEC
15	15 SCL
16	16 SDA
14	14 Reserved
18	18 +5V Power
19	19 Hot Plug Detect
SHELL	SHELL

RoHS Compliant

ORDERING INFORMATION:

- 19 01153 - * * *
- [1] [2] [3] [4] [5]
- [1] SERIES NUMBER:
19:Adapter Series
- [2] SEQUENCE NO.:
01153(EX. 01001-01999):HDMI (A)MALE TO
(A)FEMALE ADAPTER(270 Degree)
- [3] OUTER MOLDING COLOR CODES:
2:Gray(P.T.432C) 3:Black 4:White
6:Blue 7:Red 9:Yellow
- [4] Plating of contact&shell:
1:Contact plated gold 30u";Shell plated G/F
2:Contact plated gold 30u";Shell plated nickel
3:Contact plated gold 15u";Shell plated G/F
4:Contact plated gold 15u";Shell plated nickel
- [5] SUFFIX NO.:
H:With HDMI logo
N:Empty logo
S:With special logo(customer logo)

VPI VIDEO
PRODUCTS
INCORPORATED

1275 Danner Drive Aurora, Ohio 44202
Tel: 1-800-626-7801 Fax: 330-562-1999
www.vpi.us sales@vpi.us