



ELECTRONIC TEST:

- 1.OPEN/SHORT/INTERMITTE:100%.
- 2.INSULATION RESISTANCE:5MΩ
- 3.CONTACT RESISTANCE:10Ω
- 4.HI-POT:300V 10MS

SHIELD	SHIELD	GROUND
PIN24	PIN24	TMDS CLOCK-
PIN23	PIN23	TMDS CLOCK+
PIN22	PIN22	TMDS CLOCK SHIELD
PIN21	PIN21	TMDS DATA 5+
PIN20	PIN20	TMDS DATA 5-
PIN19	PIN19	TMDS DATA 0/5 SHIELD
PIN18	PIN18	TMDS DATA 0+
PIN17	PIN17	TMDS DATA 0-
PIN16	PIN16	HOT PLUG DETECT
PIN15	PIN15	GROUND(+5V & HV SYNC)
PIN14	PIN14	POWER +5V
PIN13	PIN13	TMDS DATA 3+
PIN12	PIN12	TMDS DATA 3-
PIN11	PIN11	TMDS DATA 1/3 SHIELD
PIN10	PIN10	TMDS DATA 1+
PIN9	PIN9	TMDS DATA 1-
PIN7	PIN7	DDC DATA
PIN6	PIN6	DDC CLOCK
PIN5	PIN5	TMDS DATA 4+
PIN4	PIN4	TMDS DATA 4-
PIN3	PIN3	TMDS DATA 2/4 SHIELD
PIN2	PIN2	TMDS DATA 2+
PIN1	PIN1	TMDS DATA 2-
DVI 24+1	DVI 24+1	CABLE FUNCTION

4	4#40 SCREW	4	pcs
3	P.V.C MOLDING BLACK IN COLOR		
2	DVI 24+1 MALE SOLDER COLOR:BLACK CONTACT PLATED:NICKEL	2	pcs
1	ROTOR MADE OF ABS SHELL RED AND WHITE	1	pcs
NO.	DESCRIPTION	Q'TY	UNITS
		09/11/06	

UNLESS OTHERWISE SPECIFIED TOLERANCE	
ANG.	±5°
0.	±0.5
.0	±0.3
.00	±0.2
SCALE:	UNIT: mm
DRAWN	09/11/06
CHECKED	09/11/06
APPROVED	
SIZE A4	REV. A

DRAWN NAME:	
PRODUCT NO.	
FILE NAME:	



1275 Danner Drive Aurora, Ohio 44202
 Tel: 1-800-626-7801 Fax: 330-562-1999
 www.vpi.us sales@vpi.us