

PIN ASSIGNMENT:

MINI HDMI/M	MINI HDMI/M
3	3 TMS data2-
2	2 TMS data2+
1	1 TMS data2 Shield
6	6 TMS data1-
5	5 TMS data1+
4	4 TMS data1 Shield
9	9 TMS data0-
8	8 TMS data0+
7	7 TMS data0 Shield
12	12 TMS Clock-
11	11 TMS Clock+
10	10 TMS Clock Shield
13	13 DDC/CEC Ground
14	14 CEC
15	15 SCL
16	16 SDA
17	17 Reserved
18	18 +5V Power
19	19 Hot Plug Detect
SHELL	SHELL

. ELECTRICAL CHARACTER:

- 100% OPEN&SHORT TESTING;
- WITHSTANDING VOLTAGE:DC 300V 0.01Sec;
- INSULATION RESISTANCE:10M Ohm(Min);
- CONDUCTIVE RESISTANCE:2 Ohm(Max).

4	OVERMOLD	PVC 70P BLACK UL94V-0	
3	INNERMOLD	PE LOW DENSITY	
2	CONNECTOR	MINI HDMI 15U" /AU BLACK SHELL G/F PLATED	
1	HDMI CABLE	UL20276(1P*30#+AL+D+MYLAR)*4C+1P*30#+5C*30#+AL+B OD5.5mm JACKET:PVC BLACK 1.3REV Impedance:100ohm	
NO.	PART NAME	SPEC DESCRIPTION	REMAKE

VPI VIDEO PRODUCTS INCORPORATED

1275 Danner Drive Aurora, Ohio 44202
Tel: 1-800-626-7801 Fax: 330-562-1999
www.vpi.us sales@vpi.us