

CAT6 Bulk Cables

www.vpi.us/c/cat6-bulk-cables-193

CAT6 Solid Unshielded Bulk Cable



CAT6-BULK-COLOR

- Flame-retardant PVC jacket and polyolefin insulation.
- CMR-rated for all general in-wall and riser use.
- Meets or exceeds ANSI/TIA/EIA-568-B.2-1 Category 6 and ISO/IEC 11801, Class E requirements
- Conductor: Solid
- Gauge: 23 AWG
- OD: 0.248 ± .012"
- 250 MHz
- Operating temperature: -4 to 167°F (-20 to 75°C)
- Supports full and half-duplex operation.
- Tested for electrical performance.
- Easy to use pull box.
- Length: 1,000 feet

CAT6 Solid Shielded Bulk Cable, 550 MHz, CMR-Rated



CAT6-BULK-STP-BLUE550

- Flame-retardant PVC jacket and polyolefin insulation.
- CMR-rated for all general in-wall and riser use.
- Meets or exceeds ANSI/TIA/EIA-568-B.2-1 Category 6, UL, CSA and ISO/IEC 11801 requirements
- Conductor: solid
- Gauge: 23 AWG
- 550 MHz
- 1,000 feet on wooden spool
- Supports full and half-duplex operation.
- Tested for electrical performance.
- Easy to use pull box.
- Length: 1,000 feet
- Color: blue.

CAT6 Stranded Unshielded Bulk Cable, CM-Rated



CAT6-BULK-GRAY-STRND

- Flame-retardant PVC jacket and polyolefin insulation.
- CM-rated for in-wall use.
- Meets or exceeds ANSI/TIA/EIA-568-B.2-1 Category 6 and ISO/IEC 11801, Class E requirements
- Conductor: Stranded
- Gauge: 24 AWG
- OD: 0.252 ± .012"
- 250 MHz
- Supports full and half-duplex operation.
- Tested for electrical performance.
- Easy to use pull box.
- Length: 1,000 feet
- Color: gray

CAT6 Solid Shielded Bulk Cable



CAT6-BULK-STP-COLOR

- Flame-retardant PVC jacket and polyolefin insulation.
- Meets or exceeds ANSI/TIA/EIA-568-B.2-1 Category 6 and ISO/IEC 11801, Class E requirements
- Conductor: Solid
- Gauge: 23 AWG
- OD: 0.256 ± .007"
- 250 MHz
- Supports full and half-duplex operation.
- Tested for electrical performance.
- Easy to use pull box.
- Length: 1,000 feet
- Regulatory approvals: RoHS, UL, ETL verified.

CAT6 Bulk Cables

www.vpi.us/c/cat6-bulk-cables-193

CAT6 Plenum Solid Unshielded Bulk Cable, CMP-Rated



CAT6-BULK-PLNM-GRAY

- Flame-retardant plenum jacket and polyolefin insulation.
- Meets or exceeds ANSI/TIA/EIA-568-B.2-1 Category 6 and ISO/IEC 11801, Class E requirements
- Gauge: 23 AWG
- CMP-rated for use in air-handling ducts and plenums
- Conductor: Solid
- OD: 0.236 ± .007"
- 550 MHz
- Supports full and half-duplex operation.
- Tested for electrical performance.
- Easy to use pull box.
- Length: 1,000 feet

CAT6 Super Flat Stranded Bulk Cable, Unshielded - 250 ft



CAT6-SF-BULK-BLACK

- These super flat CAT6 noodle cables are only 0.06" thick and are ideal for hiding under carpets.
- Supports full and half-duplex operation.
- Tested for electrical performance.
- Flame-retardant PVC jacket and polyolefin insulation.
- Meets or exceeds ANSI/TIA/EIA-568-B.2-1 and ISO/IEC 11801, Class E requirements
- Gauge: 28 AWG
- Thickness: 0.06"
- Max length for data transfer: 65 feet (20 meters)
- Color: Black only

CAT6 CMXT Outdoor Direct Burial Solid Shielded Bulk Cable



CAT6-BULK23-STP-ODB-BLACK

- Excellent for harsh environments, indoor or outdoor.
- Ideal for connecting to servers located in another building.
- Linear low-density polyethylene jacket and polyethylene insulation.
- Meets or exceeds TIA/EIA-568B.2-1 Category 6, ISO/IEC 11801 Class E, CAN/CSA-C22.2 No. 214 requirements.
- Conductor: Solid.
- Length: 1,000 feet.
- Gauge: 23 AWG.
- OD: 0.323" ± .012"
- 600 MHz.
- Resistant to UV, most chemicals, impact, puncture, cold and cracking.
- Supports full and half-duplex operation.
- Tested for electrical performance.
- Easy to use pull box.
- Length: 1,000 feet
- Color: black.

CAT6 Ultra Super Flat Stranded Bulk Cable, Unshielded - 250 ft



CAT6-USF-BULK-BLACK

- These ultra super flat CAT6 noodle cables are only 0.04" thick and are ideal for hiding under carpets.
- Supports full and half-duplex operation.
- Supports POE up to 15 meters.
- POE Class 3, 15.4W max.
- Tested for electrical performance.
- Flame-retardant PVC jacket and polyolefin insulation.
- Meets or exceeds ANSI/TIA/EIA-568-B.2-1 and ISO/IEC 11801, Class E requirements.
- Gauge: 32 AWG
- Thickness: 0.04"
- Width: 0.15"
- Length: 250 feet
- Color: Black.
- Ideal for hiding under carpet.
- Use a utility knife to carefully score the cable jacket for plug assembly.