

Thin VGA Cables

www.vpi.us/c/thin-vga-20

Super Thin VGA Monitor Cable



VEXT-THN-xx

- No ghosting and no degradation - guaranteed.
- Diameter: 0.225".
- Ideal for applications where space is tight.
- Gold plated contacts.
- Supports 1920x1200 (WUXGA) video resolution up to 25 feet.
- Supports 1280x1024 (SXGA) video resolution up to 50 feet.
- Wire gauge: 30AWG
- Three 75 ohm micro coaxial cables.
- The shield consists of mylar foil, braided shield and drain wire.
 - Drain wire and braid connected to connector shell.
- Male 15HD to female 15HD extension VEXT-THN-xx.
- Available lengths: 6/10/25/35/50 feet.
- Male 15HD to male 15HD interface VEXT-THN-xx-MM.
- Available lengths: 15/25/35/50 feet.

Ultra Thin VGA Monitor Cable with Ferrites - Male-to-Male - 3/6/10/15/25/50 ft



VEXT-UTHN-F-xx-MM

- Ferrite cores at each end protect against EMI and RFI interference.
- No ghosting and no degradation – guaranteed.
- Diameter: 0.200".
- Ideal for applications where space is tight.
- Three 75 ohm micro coaxial cables.
- The shield consists of mylar foil, braided shield and drain wire.
- Shallow backshell.
- Supports 1920x1200 (WUXGA) video resolution.
- Same video transmission quality as traditional thicker monitor cable.
- The conductors for the three color lines are 30AWG coaxial, while the remaining conductors are 32AWG stranded wire.
- Male 15HD to male 15HD interface.
- Available lengths: 3/6/10/15/25/50 feet.

Ultra Thin VGA Monitor Cable - Male-to-Male - 1.5 ft



VEXT-UTHN-1-5-MM

- No ghosting and no degradation – guaranteed.
- Diameter: 0.200".
- Ideal for applications where space is tight.
- Gold plated contacts.
- Three 75 ohm micro coaxial cables.
- The shield consists of mylar foil, braided shield and drain wire.
- Shallow backshell.
- Supports 1920x1200 (WUXGA) video resolution.
- Same video transmission quality as traditional thicker monitor cable.
- The conductors for the three color lines are 30AWG coaxial, while the remaining conductors are 32AWG stranded wire.
- Male 15HD to male 15HD interface.
- Available length: 1.5 feet.

Thin VGA Monitor Cables with Gold Connectors & Ferrites



VEXT-THN-GF-XX

- Gold plated connectors for smooth, corrosion-free connections.
- Ferrite cores at each end protect against EMI and RFI interference.
- Diameter: 0.236"
- No ghosting and no degradation – guaranteed.
- Ideal for applications where space is tight.
- The shield consists of mylar foil, braided shield and drain wire.
- Shallow backshell.
- Supports 1920x1200 (WUXGA) video resolution up to 50 feet.
- The conductors for the three color lines are 30AWG coaxial, while the remaining conductors are 32AWG stranded wire.
- Male 15HD to female 15HD extension, VEXT-THN-GF-xx
- Male 15HD to male 15HD interface VEXT-THN-GF-xx-MM.
- Available lengths: 1.5/3/6/10/15/25/35/50 feet.