

NEMA 5-15P Power Cords

www.vpi.us/c/nema-515p-337

18 AWG 3-Slot Polarized Laptop Power Cord, NEMA 5-15P to IEC 320 C5



PWR-CRD18-515PC5-6

- Plug into laptops, portable projectors, iMac G4s and other polarized devices that use the 3-slot, cloverleaf connector.
- Length: 6 ft.
- Connectors:
 - Supply end: NEMA 5-15P
 - Equipment end: IEC 320 C5
- Wire gauge: 18 AWG
- Amp rating: 10A
- Voltage rating: 125V
- Cable jacket: SVT
- Regulatory approvals: UL

14 AWG Universal Angled Power Cord, Left Angled NEMA 5-15P to Straight IEC 320 C13



PWR-CRD14-LAS-515PC13-6

- Angled 90-degree NEMA 5-15P connector enables easy installation in tight spots.
- Plug into PCs, monitors, scanners, printers and other devices that use the 3-pin shrouded power connector.
- Length: 6 ft.
- Connectors:
 - Supply end: NEMA 5-15P, left angled.
 - Equipment end: IEC 320 C13R, straight.
 - ◆ When plugged in, the cable extends to the left.
- Wire gauge: 14 AWG
- Amp rating: 15A
- Voltage rating: 125V
- Cable jacket: SJT
- Regulatory approvals: UL

14 AWG Universal Angled Power Cord, Straight NEMA 5-15P to Left Angled IEC 320 C13



PWR-CRD14-SLA-515PC13-xx

- Angled 90-degree connector enables easy installation in tight spots.
- Plug into TVs, PCs, monitors, scanners, printers and other devices that use the 3-pin shrouded power connector.
- Available lengths: 3/6/15 feet
- Connectors:
 - Supply end: NEMA 5-15P, straight.
 - Equipment end: IEC 320 C13, left angled.
 - ◆ When plugged in, the cable extends to the left.
- Wire gauge: 14 AWG
- Amp rating: 15A
- Voltage rating: 125V
- Cable jacket: SJT
- Regulatory approvals: UL

18 AWG Universal Power Cord, NEMA 5-15P to IEC 320 C13



PWR-CRD18-515PC13-xx

- Plug into PCs, monitors, printers, scanners and other devices that use the 3-pin shrouded power connector.
- Available lengths: 1/1.5/3/6 feet.
- Connectors:
 - Supply end: NEMA 5-15P
 - Equipment end: IEC 320 C13
- Wire gauge: 18 AWG
- Amp rating: 10A
- Voltage rating: 125V
- Cable jacket: SVT
- Regulatory approvals: UL

NEMA 5-15P Power Cords

www.vpi.us/c/nema-515p-337

18 AWG Hospital Grade Power Cord, NEMA 5-15P to IEC 320 C13



PWR-CRD18HG-515PC13-xx

- Plug into PCs, monitors, printers, lab equipment and other devices that use the 3-pin shrouded power connector in a harsh hospital environment.
- Connectors:
 - Supply end: NEMA 5-15P
 - Equipment end: IEC 320 C13
- Wire gauge: 18 AWG
- Amp rating: 10A
- Voltage rating: 125V
- Available lengths: 6/10 feet.
- Regulatory approvals: cUL, UL
- Cable jacket: SJT

18 AWG Universal Angled Power Cord, Straight NEMA 5-15P to Left Angled IEC 320 C13



PWR-CRD18-SLA-515PC13-xx

- Angled 90-degree connector enables easy installation in tight spots.
- Plug into PCs, monitors, scanners, printers and other devices that use the 3-pin shrouded power connector.
- Available lengths: 3/6/10/15 feet
- Connectors:
 - Supply end: NEMA 5-15P, straight.
 - Equipment end: IEC 320 C13, left angled.
 - ◆ When plugged in, the cable extends to the left.
- Wire gauge: 18 AWG
- Amp rating: 10A
- Voltage rating: 125V
- Cable jacket: SVT
- Regulatory approvals: UL

18 AWG NEMA 5-15P to Unterminated ROJ Power Cord, High Temperature



PWR-CRD18HT-515PROJ-6

- Use standard ROJ wires for special power applications that use the three conductors (black, white and green).
- Available Length: 6 ft.
- Connectors:
 - Supply end: NEMA 5-15P
 - Equipment end: Unterminated – outer jacket stripped 1”.
- Wire gauge: 18 AWG
- Amp rating: 10A
- Voltage rating: 300V
- Cable jacket: SVT
- Max. operating temperature: 221°F (105°C)
- Regulatory approvals: UL