

HDMI to VGA + Audio Converter Adapter

www.vpi.us/av-converters/hdmi-vga-adapter-1790

- Connects a computer, laptop, tablet, or other device with HDMI connector to an analog VGA monitor or projector.
- Built-in chipset that converts digital to analog signals.
- Supports 2K resolution 2048x1080, HDTV resolutions to 1080p, and up to 1920x1200 (WUXGA).
- Compact design – connects directly to HDMI source.
- Supports EDID pass-through.
- No external power supply required.
 - Features a USB Micro B connector that provides additional power to the converter if needed.



HD-VGAA-CNVTR-V2

The HDMI to VGA + Audio Converter changes a computer's digital HDMI signal to analog VGA video and stereo audio. The converter generates all of the compatible digital to analog conversion signals to make the connection between the HDMI input and the VGA output work.

Specifications

Video

- One male HDMI connector for video source.
- One female 15-pin HD connector on attached 3.94-inch (100 mm) cable for monitor.
- One female 3.5mm jack for 2-channel stereo audio speakers.
- Supports 2K resolution 2048x1080, HDTV resolutions to 1080p, and up to 1920x1200 (WUXGA).

Power

- No external power supply required.
- One female USB Type Micro B connector – provides additional power to the converter if needed.

Dimensions

- WxDxH: 1.7x1.78x0.59 in (43.2x45.2x15 mm)
- Cable length: 3.94 inches (100 mm)

Environmental

- Operating temperature: 32 to 113°F (0 to 45°C)

Regulatory Approvals

- CE, RoHS.

Cables

- Use VEXT-1-5/3/6/10/15/25-MM VGA Male-to-Male Cable without Ferrites to connect a VGA display.
- Use VEXT-F-1-5/6/10/15/25/35/50-MM VGA Male-to-Male Cable with Ferrites to connect a VGA display.
- Cables not included.

