

Industrial USB 3.0 Hub, 7-Port

www.vpi.us/usb-hubs/usb3-hub-industrial-7port-2009

- Connect up to seven USB 3.0 self-powered and/or bus-powered USB peripheral devices (security cameras, printers, scanners, touch screen monitors, game controllers, flash drives, keyboards, mice, etc.).
- Ideal for industrial applications in harsh environments at high temperatures up to 158°F (70°C).
- Compliant with USB 3.0 SuperSpeed specifications.
 - Backwards compatible with USB 2.0/1.1/1.0
 - Supports super-speed (5 Gbps), high-speed (480 Mbps), full-speed (12 Mbps), or low-speed (1.5 Mbps) USB devices.
- Each port supports full 900mA current.
- Supports Plug-n-Play specification.
- Hot-swappable.
- Cascade hubs to connect up to 127 devices.
- No drivers required.
- Integrated mounting brackets for easy surface/wall mounting.
- High quality, rugged steel construction with durable powder coat finish.



USB3-HUB-IND-7

The Industrial USB 3.0 7-Port Hub connects up to seven USB 3.0 SuperSpeed peripheral devices to a PC or MAC computer in a harsh environment.

Specifications

Connectors

- Seven female USB 3.0 Type A connectors.
 - Supports SuperSpeed (5 Gbps), high-speed (480 Mbps), full-speed (12 Mbps), or low-speed (1.5 Mbps) USB devices.
- One female USB Type B connector.
 - Supports USB-enabled computers (PC and MAC).
 - Multiplatform support: Windows 7/8/8.1/10, Linux, and MAC OS 10.7 and higher.

Power

- Input: 110 to 220 VAC at 50 or 60Hz via AC adapter (included).
- Output: 16VDC, 3A
- Each port supports full 900mA current.
 - Overcurrent protection for each downstream port.

Environmental

- Operating temperature: 32°F to 158°F (0°C to 70°C).
- Storage temperature: -13°F to 185°F (-25°C to 85°C).

Dimensions

- WxDxH (in): 7.28x3.15x0.91 (185x80x23 mm).

Regulatory Approvals

- CE, FCC, RoHS

Package Includes

- 7-Port USB 3.0 Hub
- Power adapter
- 2.15 ft (655 mm) USB 3.0 Type A male to USB 3.0 Type B male cable.