

4-Port USB 3.1 Hub, Metal Enclosure

www.vpi.us/usb-hubs/usb3-hub-4port-10gbps-2010

- Connect up to two USB 3.1 Type C and two USB 3.1 Type A SuperSpeed+ peripheral devices (keyboard, mouse, touchscreen, flashdrive, webcam, game controllers, etc.) to a computer.
- Compliant with USB 3.1 Gen 2 SuperSpeed+ specifications.
 - Backwards compatible with USB 3.0/2.0/1.1/1.0
 - Supports SuperSpeed+ (10 Gbps), SuperSpeed (5 Gbps), high-speed (480 Mbps), full-speed (12 Mbps), or low-speed (1.5 Mbps) USB devices.
- Each port supports full 900mA current.
- Supports Plug-n-Play specification.
- Hot-swappable.
- Cascade hubs to connect up to 127 devices.
- No drivers required.
- Integrated mounting brackets for easy surface/wall mounting.
- High quality, rugged steel construction with durable powder coat finish..



USB3-HUB-2C2A

The 4-port USB 3.1 Hub connects up to two USB 3.1 Type C and two USB 3.1 Type A SuperSpeed+ peripheral devices to a PC or MAC computer.

Specifications

Connectors

- Two female USB 3.1 Type A connectors for peripheral devices.
- Two female USB 3.1 Type C connectors for peripheral devices.
- One female USB 3.1 Type C connector for PC or MAC computer.
 - Multiplatform support: Windows 7/8/8.1/10, Linux, and MAC OS 10.7 and higher.

Power

- Input: 110 to 220 VAC at 50 or 60 Hz via AC adapter (included).
- Output: 5VDC, 4A
- If additional power is required, a 5V, >4A power supply can be wired to the screw terminal pair and used instead.
- Power consumption: 15W max
- Each port supports full 900mA current.
 - The overall maximum power the hub can supply to peripheral USB devices is 13.5W.
 - Overcurrent protection for each downstream port.

Environmental

- Operating temperature: 32°F to 122°F (0°C to 50°C).
- Storage temperature: -13°F to 158°F (-25°C to 70°C).

Dimensions

- WxDxH (in): 5.3x2.88x1.04 (135x73x27 mm)

Regulatory Approvals

- CE, FCC, RoHS

Package Includes

- 4-Port USB 3.1 Hub
- Power adapter
- 2.05 ft (625 mm) USB 3.1 Type C male-to-male cable.