

Pr

Customer Spec

VPI P/N: CAT6-RASV2-xx-GRAY-SHLD

LENGTH

Ø6.2mm

29.00

14.00

25.85

16.45

29.75

15.40

44.00

Length-Ft (mm)	Tolerance:+/-In. (mm)
2 (610)	1.18 (30)
9 (2743)	2.36 (60)

RJ45 M ale(Shield)

UNITS: Millimeters

P1
8P8C

P2
8P8C

1 WHITE/ORANGE
2 ORANGE
3 WHITE/GREEN
6 GREEN
4 BLUE
5 WHITE/BLUE
7 WHITE/BROWN
8 BROWN
SHELL SHELL-DRAIN WIRE

No.	Component	Description
1	CABLE	CAT6 4P*24 AWG(7/0.20BC) WITH DIVIDER+AL+DRAIN WIRE+PVC JACKET, O.D.=6.2MM 60°C GRAY
2	CONN.	RJ45 8P8C PLUG,SHELL:NICKEL PLATED, CONTACT:GOLD PLATED 15μ"
3	BOOT	LDPE, SNAGLESS
4	BOOT	PVC 90P GRAY , SNAGLESS
5	CONSTRUCT.	CABLE WITH OVERALL SHIELD AND DRAIN WIRE BUT WITH UNSHIELDED INDIVIDUAL STRANDED TWISTED PAIR RoHS COMPLIANT
6	MARKINGS ON JACKET	AWM 2835, 24AWG,60°C 30V,FT2 ,<UL FILE #>, ETL VERIFIED, CAT6 FTP TIA/EIA 568B.2-1, CM, 4PR CABLE

VPI VIDEO PRODUCTS INCORPORATED

1275 Danner Drive Aurora, Ohio 44202
Tel: 1-800-626-7801 Fax: 330-562-1999
www.vpi.us sales@vpi.us