


CAT7-FLT-BULK-300M-BLK

CABLE SPECIFICATION

SPEC No.:	CAT7 FLAT {32AWG(7/0.08BC)WITH 1P+A}×3C +{32AWG(7/0.08BC)WITH 1P+D(7/0.1TIN COPPER)+A}×1C												
Customer:		Style:		Date	2024-07-24	REV.	1.0	DESCRIP	DATA SHEET		No.	2030306X	
Construction Item								A					
Conductors		Construction AWG				AWG		4P:32#(7/0.08)					
		Material						BARE COPPER+150D					
		Pitch				mm		2.45		2.45		2.45	
Insulators		Material						HD-PE		HD-PE		HD-PE	
		Diameter				mm		0.78 ± 0.05		0.78 ± 0.05		0.78 ± 0.05	
		Average Thickness				mm		0.26		0.26		0.26	
		Color						WHITE & ORANGE		WHITE&GREEN		WHITE & BLUE	
Outside Layer		Pitch				mm		14.0±0.3		11.67±0.3		11.67±0.3	
		Filer Material						_____		_____		_____	
		Direction						_____		_____		_____	
Outside-Tape Wrap		Pitch				mm		_____		_____		_____	
		Material						AL-foil (6*0.025)		AL-foil (6*0.025)		AL-foil (6*0.025)	
		Conductive Side						Inside		Inside		Inside	
Drain wire		Overlap Rate				%		25		25		25	
		Construction AWG				AWG		_____		_____		7/0.1	
Outside-Shield		Material						_____		_____		TIN COPPER	
		Shield						_____					
		Construction AWG						_____					
		Conductors Size				mm		_____					
		Material						_____					
Outside Jacket		Coverage				%		_____					
		Material						50P PVC					
		Diameter				mm		(2.2± 0.15)*(7.2± 0.15)mm					
		Average Thickness				mm		_____					
		Extrusion						Extrusion					
		Surface						Smooth					
Marking		Color				WHITE		Font				High	
		CAT7 FLAT CABLE RoHS											



CONDUCTORS:32AWG(7/0.08)×4P WITH
BARE COPPER

HD-PE ,ID:0.78± 0.05mm

ALUMINUM FOIL

DRAIN SHIELD(7/0.1TC)

PVC OUTER JACKET COLOR: BLACK
OD:(2.2± 0.15)*(7.2± 0.15)MM

CORD SPECIFICATION